

Silkolene®

SILKOLENE COMP 2 PLUS

Fully synthetic, ultra-low smoke 2-Stroke oil for high performance motorcycles

Description

SILKOLENE COMP 2 PLUS is a fully synthetic, ester, competition 2-stroke oil formulated for modern high performance on and off road, 2-stroke engines. SILKOLENE COMP 2 PLUS is a clean burning formula that ensures freedom from plug fouling and heavy combustion chamber deposits in vital areas such as rings and ports. It minimises lacquer on pistons and power valves giving more efficient combustion. SILKOLENE COMP 2 PLUS is also ultra-low smoke providing maximum, clean, performance, extra power and reliability. SILKOLENE COMP 2 PLUS reduces friction and wear under high stress use and ensures a high degree of internal engine cleanliness for optimum performance retention. SILKOLENE COMP 2 PLUS is compatible with all fuels and can be used for both pre-mix and injector systems

Application

SILKOLENE COMP 2 PLUS is ideal for all modern 2-stroke engines, on road, on track and off road including motocross. SILKOLENE COMP 2 PLUS is also suitable for both air and liquid cooled engines.

SILKOLENE COMP 2 PLUS is generally recommended for use at ratio of between 2 - 3% however users are advised to always follow engine manufacturers' recommendations for fuel / oil ratio

SILKOLENE COMP 2 PLUS should **NOT** be mixed with other oils, but is compatible with all leaded and unleaded fuel.

Advantages

- Suitable for high performance 2-stroke engines on track, on road and off road
- High film strength offers minimised friction and maximum power output
- Advanced additive technology provides performance retention for the life of the oil
- Excellent anti-wear characteristics help prolong engine life
- Very low ash additive system promotes clean burning
- Ultra low smoke for better environmental acceptance

Specifications

- JASO FC / FD
- ISO L-EGD
- API TC

Product Information



Further Information

Typical Data: SILKOLENE COMP 2 PLUS

Characteristics	Test Method	Unit	Result
Specific Gravity at 15°C	IP160		0.880
Kinematic Viscosity @ 40°C	IP71	mm ² /s	76.6
Kinematic Viscosity @ 100°C	IP71	mm ² /s	11.7
Viscosity Index (VI)	IP226		147
Flash point		°C	
Pour point	IP15	°C	

Reviewed 21/04/2020 AB

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.